

BEST AVAILABLE COPYIN THE CLAIMS

Please amend/replace claim 1 and cancel claims 2-16.

Claim 1 (amended): A tool for removal of removing a damaged spark/glow plug, the damaged spark plug having an electrode end, an electrical connector end, and an insulator therebetween, ~~the plug further having~~ a damaged or missing wrench-engaging member having a ~~pre-damaged width across corners diameter and~~ disposed between about the insulator ~~and the electrode end~~, the ~~plug further having~~ and a body adjacent the depending away from the damaged wrench-engaging member ~~or a position previously occupied by~~ the wrench-engaging member, the body having ~~a reduced diameter from a periphery smaller than a periphery of an undamaged~~ the wrench-engaging member width-across-corners diameter, the tool comprising:

a body portion extending along a first direction, the body portion having a first end, a second end, and an aperture extending from the first end into the body portion toward the second end, the aperture defining an interior surface configured to engage a portion of the body of the damaged spark plug adjacent the damaged wrench-engaging member for rotating and removing the damaged spark plug, wherein a length of the aperture in the first direction is greater than or equal to a distance from the electrical connector end to the damaged wrench-engaging member

a plug engaging and having an interior surface having a geometry adapted to cut into the body of the spark/glow plug; and

an end opposed to the plugging engaging and in adapted to be matingly engageable with a wrench.

Claims 2-16 (cancelled).

BEST AVAILABLE COPY

Please add new claims 17-23.

Claim 17 (new): The tool of claim 1, wherein the interior surface has a threaded portion.

Claim 18 (new): The tool of claim 17, wherein a first thread direction of the threaded portion is opposite a second thread direction of a threaded portion of the spark plug proximate the electrode end.

Claim 19 (new): The tool of claim 18, wherein the threaded portion further has at least one groove.

Claim 20 (new): The tool of claim 1, wherein the interior surface further has at least one spline portion.

Claim 21 (new): The tool of claim 1, wherein the second end is configured to receive a torque application device.

BEST AVAILABLE COPY

Claim 22 (new): A method of removing a damaged spark plug from an engine utilizing a tool, the damaged spark plug having a damaged wrench-engaging member and a body disposed adjacent the wrench-engaging member, the tool having a body portion extending along a first direction, the body portion having a first end, a second end, and an aperture extending from the first end into the body portion toward the second end, the aperture defining an interior surface configured to engage a portion of the body of the damaged spark plug adjacent the damaged wrench-engaging member, the method comprising:

- disposing the tool proximate the spark plug such that the interior surface of the tool contacts the body of the damaged spark plug adjacent the damaged wrench-engaging member;

- connecting a torque application device to the second end of the tool; and

- rotating the torque application device in a first direction to rotate the tool and the damaged spark plug to remove the damaged spark plug from the engine.

Claim 23 (new): The method of claim 22, further comprising:

- rotating the torque application device in a second direction opposite the first direction to further engage the interior surface of the tool into an exterior surface of the body of the damaged spark plug.